









## PCX 12/36 & 13/40 PLATE COMPACTORS





ALTRAD BELLE RESERVES THE RIGHT TO AMEND OR IMPROVE ANY SPECIFICATIONS IN THIS BROCHURE WITHOUT NOTICE.







- Foldable mounted guide handle offers superior manoeuvrability and can be lowered to operate under obstacles and close to form work.
- Reinforced centrifugal clutch ensures longer belt life, and simplified belt adjustment.
- Lifting points and front lift cage offer easier loading and unloading for operator convenience.
- Large 9.5 litre water tank is built into the protective frame.
- Choice of Honda or Loncin petrol engines.
- Angled holes on spray bar allow complete water coverage over the full width preventing any asphalt pick-up on plate
- The spraybar is fully protected from damage, easily positioned, with integral paving pad clamp points.
- Life lubricated vibration bearings.



WATER SPRAY KIT OPTION **AVAILABLE** 



WHEEL KIT OPTION AVAILABLE

## **TECHNICAL SPECIFICATIONS**

Model	PCX 12/36	
Plate Width	(mm)	360
Plate Length	(mm)	720
Centrifugal Force	(kN)	12
Travel Speed	(m/min)	20
Vibration level	(m/sec²)	4.74
Noise Level	(dB(A)	105

Honda GX120 Model PCX 12/36 Part No. FC3600E **Engine Power** (Hp/kW) 4.0/3.0Weight (kg) 81 Static Pressure  $(kg/m^2)$ 586

PCX 12/36 Block Paving Pad

PCX 13/40 Block Paving Pad

PCX 12/36 Water Spray Kit

PCX 13/40 Water Spray Kit

PCX 12/36 & 13/40 Wheel Kit

Model PCX 13/40 Plate Width (mm) 400 Plate Length (mm) 606 Centrifugal Force (kN) 13 **Travel Speed** (m/min) 20 Vibration level  $(m/sec^2)$ 3.20 Noise Level (dB(A)

Model PCX 13/40 Part No. **Engine Power** Weight Static Pressure

Model PCX 13/40

Part No. **Engine Power** Weight Static Pressure

Model PCX 13/40

Part No. **Engine Power** Weight Static Pressure

Honda GX120 FC4000E (Hp/kW) 4.0/3.0(kg) 83.5  $(kg/m^2)$ 520

Honda GX160 FC4020E (Hp/kW) 5.5/4.085.5 (kg)  $(kg/m^2)$ 518

Loncin H135 FC4060E (Hp/kW) 3.5/2.6 83.5 (kg)  $(kg/m^2)$ 520



**Options** OPP/65/DIO

OPP/66/DIO

OPP/74/DIO

OPP/70S/DIO

OPP/71S/DIO









