





The all-rounder

The 1001 is the perfect solution for confined spaces. The extremely compact machine is available with a 990 mm width and can fit through narrow passages. Thanks to the typical articulated pendulum joint and the low-maintenance twin-lock 4-wheel drive system, traction remains guaranteed on every terrain. The folddown roll over protection system provides a high level of safety and still ensures problem-free use and transport in narrow spaces. A wide control station and the intuitive operating concept also provide a high level of comfort on the machine. Easily reachable service accesses top off the overall package.



Twin-lock 4-wheel drive system

Articulated pendulum joint

Small dimensions



Unit 7 Willsborough Cluster Clonshaugh Business and Technology Park Dublin 17 D17 PV32

Ph: 01 847 6487 Mob: 085 111 6224 email: info@rmphire.ie www.rmphire.ie

Technical Data

Mechanical - Output Details	
Gradeability	45,0 %
Travel speed	14,0 km/h
Mechanical Details	
Length	3.080,0 mm
Width	1.180,0 mm
Height	2.580,0 mm
Weight	1.261,00 kg
Payload	1.000,0 kg
skip capacity levelled	415,0
Skip capacity heaped	525,01
Pendulum angle	15,0 °
Aggr. pwr time limited 1~(LTP)	1.230,0 - 1.500,0 kg
Engine	
Engine type	Diesel engine

Cylinder capacity	1.116,0 cm3
Effective power	17,0 KW
Nominal Engine speed	3.000,0 1/min
Standard (Effective power)	ISO 3046
Manufacturer	Yanmar
Engine designation	3TNV76
Environment Data	
Sound power LWA, guaranteed	101,0 dB(A)
Chassis	
turning radius	3.200,0 mm
articulation angle	33,0 °
hydraulikpump	axial piston pump
flow rate	84,0 l/min
Shipping and Storage	
Shipping weight	1.155,0 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Dimensions

A1	Height ROPS	2,580 mm
A4	Height of ROPS tilted	2,080 mm
В3	Width of vehicle	1,180 mm
B4	Width of skip	990 mm
D1	Wheel base	1,500 mm
E1	Rear overhang	810 mm
F1	Dumping width	510 mm
G1	Dumping height max.	465 mm
G2	Dumping height max., high tip skip raised	1,560 mm
H1	Skip height	1,230 mm
H2	Skip height tilted	1,770 mm
НЗ	Skip height tilted, high tip skip raised	2,860 mm
11	Ground clearance	270 mm